VERIFICATION STATEMENT FOR WATER SPRAYING FIRE EXTINGUISHING SYSTEM

Statement No:

DNV·GL

N14202GR

Valid for products not subject to DNV GL classification requirements.

Particulars of Product

Product Name:	Water spraying fire extinguishing system
Type designation:	FIREKILL OH-SW2
Application/context:	OH1 risks such as office Spaces and accommodation Areas
ID/Serial/Tag no:	N.A.
The product is intended for:	STOCK
Requirements are based on:	prEN 14972 Annex A, VdS Firetest Protocol for Water Mist Sidewall Sprinkler Systems

Deviations and limitations, if any, are stated on page 2 onwards.

Particulars of Vendor and Purchaser

Vendor:	Vid Fire-Kill ApS
Vendor reference:	
Purchaser:	
Purchaser reference:	

Issued at Denmark CMC on 2020-06-18



for DNV GL

This document has been digitally signed and will therefore not have handwritten signatures

> Lindelof, Kristian Surveyor

Except for any liability caused by DNV GL's gross negligence or wilful misconduct, DNV GL's maximum cumulative liability arising out of or related to the use of or reliance on this document shall be limited to USD 300 000. Form code: 71.07a Revision: 2017-01



Statement No: N14202GR

Verification extent and result

Verification extent:

Fire-fighting performance test according to prEN 14972, Annex A, VdS Firetest Protocol for Water Mist Sidewall Sprinkler Systems as of: 04/2016(Rev01).

Verification result/comments:

The VID Fire-Kill low pressure water mist system with the nozzle OH-SW2 installed with 6 x 6m spacing has been succesfully tested to the international approval test prEn14972, Annex A, VdS firetest protocol for water mist sidewall sprinkler systems with 5m ceiling height.

Report

The undersigned withnessed succesfully testing at Danish Fire Laboratories(DFL), test facility accredited to ISO 17025, on 2020-05-06 and 2020-06-03. Reference is made to DFL test report no. 200612-254-1, component test report no. 200612-254-2 of the OH-SW2 nozzle and FireKill OH-SW2 DIOM Manual no. 200527-01-01