


Description

The FIREKILLTM Model MS59 is a medium velocity water spray nozzle which delivers a full cone spray of water from the nozzle in an angle of 90° or 120°. The nozzle functions with a water pressure of 2-4 bar making it possible to utilize the nozzles in very harsh wind conditions.

Model MS59 Nozzles have a K-factor of 59 (liter/minute/√bar).

Model MS59 Medium Velocity Spray Nozzles are available with $\frac{1}{2}$ " NPT male connections.



Applications

The Model MS59 nozzle is designed for fire protection and cooling of primarily tanks, building and structures against hydrocarbon fires.

Approvals


The Model MS59 Titanium and Naval Brass nozzles are FM approved.

Technical data

General Description					
approved water pressure	2-4 bar				
Spray Angle	90° (+5%-15%)		120° (+5% -25	120° (+5% -25%)	
K-value	59,0 +10% /-0% (I/min/√bar)				
Connection	1/2" NPT male				
Nozzle material					
Standard	Titanium*	Grade 2		0,056 Kg	
	Naval Brass*	CuZn35Ni		0,102 Kg	
Options. Min. qty may apply	Stainless Steel	AISI 316		0,096 Kg	
	Super Duplex	25Cr		0,096 Kg	
Strainer material					
Standard	Stainless Steel*	AIS	AISI 316		
Optional	Titanium*	Gr	Grade 2		

NOTE: Minimum quantity may apply when ordering products with optional material and connections such as BSP or BSPT

Dimension



Only Naval Brass and Titanium nozzle w/stainless steel strainer are FM Approved

Contact

For further information on FIREKILL™ products, please contact our sales department at Sales@vidfirekill.com

Date of revision: 13-05-2024




Installation


Piping should be flushed prior to installation of the nozzles. The nozzles can be used for both fresh water and sea water applications.

Spray pattern at 2-4 Model MS59-90


Vertical



Angled 45 dg




Horizontal




Spray pattern at 2-4 Model MS59-120


Vertical



Angled 45 dg



Horizontal



VID Fire-Kill APS is not responsible for any errors or omissions, or for the results obtained from the use of this information. All information in this document is provided "as is", with no guarantee of completeness, accuracy, functionality, timeliness or of the results obtained from the use of this information.

Date of revision: 13-05-2024