


### **Description**

The FIREKILL™ Model HS43-120 is a high-speed water spray nozzle which delivers a full cone spray of water from the nozzle in an angle of 120° ±5%. The nozzles functions with a water pressure of 2-10 bar making it possible to utilize the nozzles in very harsh wind conditions.

Model HS43-120 Nozzles have a K-factor of 42.5 $\pm$ 5% (liter/minute/ $\sqrt{\text{bar}}$ ).

Model HS43-120 High Speed Nozzles are available with 1" NPT male connections. Optional connection upon request.



All internal water ways have diameters larger than 3mm. Nozzles should only be utilized in pipe systems with clean internal pipe surfaces and cavities. Nozzles should be installed in systems with a main-line water strainer with mesh size equal to or less than 3mm.

### **Applications**

The Model HS43-120 nozzle is designed for fire protection and cooling of primarily tanks, building and structures against hydrocarbon fires.

### **Approvals**


The Model HS43-120 Titanium and Naval Brass nozzles are FM approved.

### Technical data

General Description			
Approved water pressure	2-10 bar		
Spray Angle	120° ±5%.		
K-value	42,5 ±5 (I/min/√bar)		
Connection	1" NPT male		
Nozzle material			
Standard	Titanium*	Grade 2	0,12 Kg
	Super Duplex	25Cr	
Options. Min. qty may apply	Stainless Steel	AISI 316	0,18 Kg
	Naval Brass*	CuZn35Ni	0,20 Kg
Strainer material			
Standard	Stainless Steel*	AISI 316	
Optional	Titanium*	Grade 2	

NOTE: Minimum quantity may apply when ordering products with optional material and connections such as BSP or BSPT.

# Dimension



\*Only Naval Brass and Titanium nozzle w/stainless steel or titanium strainer are FM Approved




#### Contact


For further information on FIREKILL™ products, please contact our sales department at Sales@vidfirekill.com

Date of first issue: 16-11-2017 Date of revision: 08-05-2024





## Spray Pattern at 2-4 bar







## Spray Pattern at 4 bar







Spray Pattern at 5 bar







Spray Pattern at 6 bar







Spray Pattern at 7 bar







Spray Pattern at 8 bar







Spray Pattern at 9 bar









VID Fire-Kill APS is not responsible for any errors or omissions, or for the results obtained from the use of this information. All information in this document is provided "as is", with no guarantee of completeness, accuracy, functionality, timeliness or of the results obtained from the use of this information.

Date of revision: 08-05-2024